

Guard Tour Checking System TouchChecker

TC-200



TCR-200 & TCB-200



KEY Features

- Efficient Management & Supervision over Patrol, Security Checker, and Patrol Checking Point
- Dual Function for checking system : Contact iButton / Contactless RFID Reader (Selectable)
- Able to use 125Khz ASK[EM] / 13.56MHz[MIFARE] RFID Tag according to user choice for RFID Reader
- Vibration Mode Selection (Optional)
- User-friendly Data Interface using USB Port
- Long Durability & Quick Recharge Battery
- Easy Expansion : Over 10,922 Patrol Points
- Water-proofed





Specification

Checking Machine (TCR-200)

ITEM	Specification
Memory	64KByte EEPROM
ID Storage Capacity	10,922 points (ID + Time & Date stamp)
Battery	Li-Ion Battery (3.7V/1,100mA)
Operating Temperature	-20°to +54°C (-4° to +129°F)
Baud Rate	19,200bps (Default)
LED Indicator	LED for indicating check and alarm statuses
Weight	154g
Dimension (W x H x T)	50 x 128 x 25 (mm)

Data Transmitter & Charger (TCB-200)

ITEM	Specification
Material	PC
Dimension (W x H x T)	64 x 142 x 55 (mm)
Weight	120g
Data Transmission	Docking Concept
Recharging Method	Docking with TCR200
Power Adapter	AC 110V / 220V
Communication	RS232, Baud Rate of 38,400 bps

Checkingpoint Chips (i-Button) (TCP-200)

ITEM	Specification
Material	Memory chip stored inside, Button-shaped, Water-Resistant
Dimension (W x H x T)	16.3 diameter x 5.9 (mm)
Weight	2.3g
Battery	None
Storage	Unique 48-bit Serial Number (Read Only)